

# Vehicle: Capacity Specifications

AT Fluid

Service Initial Refill 5.7 qt (US)

Recommended Fluid Dexron III or Equivalent

Cooling Fluid

<For SEDAN model>

			Vehicle with M/T		Vehicle with A/T	
ANTI-FREEZE PROPORTIONING CHART	Freezing temperature	°C	-16	-36	-16	-36
		°F	3	-33	3	-33
	Anti-freeze/Anti-corrosion coolant concentration	%	30	50	30	50
	Ratio of compound to cooling water	ltr	1.26/2.94	2.10/2.10	1.25/2.91	2.08/2.08
		US pt.	2.66/6.21	4.44/4.44	2.63/6.14	4.39/4.39
		Imp pt.	2.22/5.17	3.70/3.70	2.19/5.11	3.65/3.65
COOLANT CAPACITY	Engine radiator and heater		3.60 liters (7.61/6.34 US/Imp. pt.)		3.55 liters (7.50/6.25 US/Imp. pt.)	
	Reservoir tank		0.60 liters (1.27/1.06 US/Imp. pt.)			
	Total		4.20 liters (8.87/7.39 US/Imp. pt.)		4.15 liters (8.77/7.30 US/Imp. pt.)	

<For WAGON model>

			Vehicle with M/T		Vehicle with A/T	
ANTI-FREEZE PROPORTIONING CHART	Freezing temperature	°C	-16	-36	-16	-36
		°F	3	-33	3	-33
	Anti-freeze/Anti-corrosion coolant concentration	%	30	50	30	50
	Ratio of compound to cooling water	ltr	1.41/3.29	2.35/2.35	1.40/3.25	2.33/2.33
		US pt.	2.98/6.94	4.96/4.96	2.95/6.86	4.92/4.92
		Imp pt.	2.49/5.80	4.14/4.14	2.47/5.73	4.10/4.10
COOLANT CAPACITY	Engine radiator and heater		4.10 liters (8.65/7.23 US/Imp. pt.)		4.05 liters (8.55/7.13 US/Imp. pt.)	
	Reservoir tank		0.60 liters (1.27/1.06 US/Imp. pt.)			
	Total		4.70 liters (9.92/8.29 US/Imp. pt.)		4.65 liters (9.81/8.20 US/Imp. pt.)	

<For SEDAN model>

			Vehicle with M/T		Vehicle with A/T	
ANTI-FREEZE PROPORTIONING CHART	Freezing temperature	°C	-16	-36	-16	-36
		°F	3	-33	3	-33
	Anti-freeze/Anti-corrosion coolant concentration	%	30	50	30	50
	Ratio of compound to cooling water	ltr	1.26/2.94	2.10/2.10	1.25/2.91	2.08/2.08
		US pt.	2.66/6.21	4.44/4.44	2.63/6.14	4.39/4.39
		Imp pt.	2.22/5.17	3.70/3.70	2.19/5.11	3.65/3.65
COOLANT CAPACITY	Engine radiator and heater		3.60 liters (7.61/6.34 US/Imp. pt.)		3.55 liters (7.50/6.25 US/Imp. pt.)	
	Reservoir tank		0.60 liters (1.27/1.06 US/Imp. pt.)			
	Total		4.20 liters (8.87/7.39 US/Imp. pt.)		4.15 liters (8.77/7.30 US/Imp. pt.)	

<For WAGON model>

			Vehicle with M/T		Vehicle with A/T	
ANTI-FREEZE PROPORTIONING CHART	Freezing temperature	°C	-16	-36	-16	-36
		°F	3	-33	3	-33
	Anti-freeze/Anti-corrosion coolant concentration	%	30	50	30	50
	Ratio of compound to cooling water	ltr	1.41/3.29	2.35/2.35	1.40/3.25	2.33/2.33
		US pt.	2.98/6.94	4.96/4.96	2.95/6.86	4.92/4.92
		Imp pt.	2.49/5.80	4.14/4.14	2.47/5.73	4.10/4.10
COOLANT CAPACITY	Engine radiator and heater		4.10 liters (8.65/7.23 US/Imp. pt.)		4.05 liters (8.55/7.13 US/Imp. pt.)	
	Reservoir tank		0.60 liters (1.27/1.06 US/Imp. pt.)			
	Total		4.70 liters (9.92/8.29 US/Imp. pt.)		4.65 liters (9.81/8.20 US/Imp. pt.)	

MT Fluid

Temperature Range

Temperatures Above -4 deg F

All Temperature Ranges

Lubricant / Viscosity

GL4 - SAE 80w/90

GL4 - SAE 75w/85 or 75w/90

Note: It is highly recommended to use 75w/90 GL4

Fluid Capacity

5.0 pt (US)

Oil

With Filter Change 3.3 qt (US)